



**C.F.R. s.r.l.**  
MODENA - Italy

**TECHNICAL DATASHEET**  
**3 PHASE INDUCTION MOTOR**


Stator Diameter	200
Stator Length	160
Rev.	01
Date	31-Aug-2022
Page	1

Curve Code

A00979-20012516008004TS0E-C\_field0%

	DESCRIPTION	SYMBOL	VALUE	UNIT
<b>NOMINAL</b>	Rated Power	$P_n$	9000	[W]
	Rated Speed	$n_n$	2600	[RPM]
	Rated Torque	$T_n$	33,1	[Nm]
	Rated Current	$I_n$	135	[Arms]
	Rated Duty	S2	60	[min]
	Battery Voltage	$V_{DC}$	80	[V]
	Rated Frequency	$f_n$	87	[Hz]
<b>PEAK</b>	Peak Torque	$T_p$	157	[Nm]
	Peak Current	$I_p$	416	[Arms]
	Peak Duty	S2	1	[min]
<b>FEATURES</b>	Ambient Temperature	$\vartheta_a$	from -20° to +40° C *	[°C]
	Number of poles		4	
	Insulation Class		F	
	Thermal Protection		STS1	
	Cooling System		Not Ventilated	

\* The minimum temperature -20°C is only for degree of protection IP65 or higher.





**C.F.R. s.r.l.**  
MODENA - Italy


**TECHNICAL DATASHEET**  
**3 PHASE INDUCTION MOTOR**

Stator Diameter	200
Stator Length	160
Rev.	01
Date	31-Aug-2022
Page	2

Curve Code


A00979-20012516008004TS0E-C\_field0%

**CURRENT MAP**



The data behind the dashed line are extrapolated with lower accuracy

**EFFICIENCY MAP**



The data behind the dashed line are extrapolated with lower accuracy